Card Reader

WWW.DELOCK.COM

DATA SHEET

Card Reader IDE 40pin male to 2x Compact Flash

Description

This Card Reader by Delock enables the application 2 Compact Flash cards via 40pin IDE interface. Since this Card Reader is bootable you can also use the it also as HDD and install a operating system. The Card Reader can be plugged to a free IDE female port of the motherboard by using an additional connecting cable.

Ref. 91644

EAN 4046319916443

Images

Specification

- IDE 40pin to 2x CF Card
- 40pin 2.54 mm standard IDE male connector
- For Compact Flash type I, type II and Micro-drive
- Master or Slave mode selection
- 2x mounting wholes
- +5 V floppy disk drive power connector
- Supports DMA and Ultra DMA modes. A compatible flash media card will be required to use these modes.
- Size: 60mm x 43mm

System requirement

- A free IDE 40pin port
- For DOS, Windows 3.1/NT4/98SE/ME/2000/XP/Vista, Unix, Linux

Package content

- Card reader IDE to CF card

Package

- Delock poly bag

© 2007 by Delock. Alle hier aufgeführten Namen und Zeichen sind Eigentum des jeweiligen Herstellers. Druckfehler, Änderungen, Lieferzeiten & Irrtümer vorbehalten.